

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A gateway for preventing overload of gateway resources, comprising:

a processor receiving both a present Central Processing Unit (CPU) utilization value and a ~~Central Processing Unit (CPU)~~ utilization threshold;

the processor setting a call deny flag when the present CPU utilization value is larger than the CPU utilization threshold; and

the processor detecting an incoming call and indicating refusal of the incoming call if to the incoming call caller without answering the incoming call when the deny flag is set.

2. (Previously Presented) The gateway according to claim 1 wherein the CPU utilization threshold is set to a value below a total available processing capacity of the gateway to ensure calls currently established on the gateway have access to additional gateway processing resources.

3. (Currently Amended) A method for preventing overload in a packet processing device receiving incoming telephone calls, comprising:

setting a Central Processing Unit (CPU) utilization threshold of a CPU of the gateway;

when an incoming telephone call is received, comparing a present CPU utilization value with the entered CPU utilization threshold; and

indicating refusal of the new incoming telephone call to the new incoming call caller before the new incoming telephone call is answered by the packet processing device when the present CPU utilization value is larger than the threshold.

4. (Previously Presented) The method of claim 3 including setting the CPU utilization threshold to an amount enough below a maximum CPU processing capacity to account for additional processing required for currently established calls.

5. (Previously Presented) The method of claim 3, further comprising determining the CPU utilization threshold for a bank of CPUs.

6. (Previously Presented) The method of claim 5, wherein setting is by issuing a setting command, and by saving an aspect of the setting command in non-volatile random access memory (NVRAM).

7. (Previously Presented) A computer-readable medium containing a program for preventing overload in a packet telephony gateway, the program comprising:

- a CPU utilization threshold input;

- an incoming call input when a new incoming telephone call is received;

- a present CPU utilization value input;

- gauging software for determining, when a new incoming telephone call is denoted as being received, whether a number aspect of the present CPU utilization value input is larger than a number aspect of a CPU utilization threshold input, and if so for setting a deny flag; and

- call refusing software for the packet telephony gateway to refuse the incoming call if the deny flag is set prior to and without ever answering the incoming call.

CI 8. (Original) The medium of claim 7, wherein

- the incoming call input sets a ring flag when a new incoming telephone call is received, and

- the present CPU utilization value input is updated when the ring flag is set.

9. (Previously Presented) The gateway according to claim 2 wherein the CPU utilization threshold is set to about 70 percent of the total available processing capacity of the gateway.

10. (Previously Presented) The gateway according to claim 1 wherein the processor detects the incoming call by monitoring a call ring flag.

11. (Previously Presented) The gateway according to claim 10 including updating the CPU utilization value each time the call ring flag is set.

12. (Previously Presented) The gateway according to claim 1 wherein the processor detects a ring signal for the incoming call and determines whether or not to refuse the incoming call prior to answering the ring signal.

13. (Previously Presented) The gateway according to claim 1 including refusing the incoming call by generating a busy signal.

Cl 14. (Currently Amended) The gateway according to claim 1 wherein the processor does not temporarily ~~place-refused~~ refuse incoming calls and does not place temporarily refused calls in a queue.
